



Main

Range of product	TransferPacT
Product or component type	I/O module
Device application	Signalling

Complementary

Auxiliary contact composition	Without
Signalling function	CAN extension (connect to external HMI) Output voltage (24 V)
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm ²
Mounting mode	Plug-in
Mounting position	Left-bottom
Maximum input current	1 A 24 V DC +/- 20 %
[Ui] rated insulation voltage	30 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.65 cm
Package 1 Width	6.9 cm
Package 1 Length	2 cm
Package 1 Weight	140 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.3 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information