TPSAUX33

auxiliary contact, TransferPacT, indication for OFF position





Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

Complementary

o o mpromornary		
Auxiliary contact composition	2 NO + 2 NC	
Signalling function	Switch position (off)	
Auxiliary connection terminal	Screw clamp terminal	
Mounting mode	Clip-on	
Mounting position	Right-angled	
Tightening torque	0.6 N.m +/- 0.1 N.m	
Height	90 mm	
Width	17.5 mm	
Depth	49.5 mm	
Net weight	60 g	
Accessory / separate part category	Signalling accessory	

Environment

IP degree of protection	IP20	
Pollution degree	3	

Packing Units

1 4.3 cm
5.8 cm
12.0 cm
180.0 g
S02
18
15.0 cm
30.0 cm
40.0 cm
3.5 kg
_

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information