TR25D4R2004TPE

TransferPacT Remote, 200A, 400V, 4P, Remote, frame 250A





Main

Range of product	TransferPacT
Product or component type	Remote transfer switch
Device application	Change source of supply
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
Downside connection	Screwed
Mounting mode	Fixed
Upside connection	Screwed
Contact position indicator	Yes
[lcm] rated short-circuit making capacity	30 KA switch-disconnector alone 400 V AC at 50 Hz 330 kA with upstream protection circuit breaker 400 V AC at 50 Hz
Suitability for isolation	Yes

Complementary

PC
3
1 NO + 2 NC
1 NC + 2 NO
2 NO
AC-33B
400 V AC 50/60 Hz
Remote control
Manual
Remote
Alarm indicator
Plate
Padlock in OFF position
Padlock in SI / SII position
Uninterrupted
Switch: 800 V
Controller: 500 V
Switch: 8 kV
Controller: 6 kV
200 A
With mechanical interlocking
10000 cycles
35 mm
LED indicator (green) for power ON
LED indicator (red) for alarm
10 KA during 0.5 s
15 kA during 0.1 s
341 Mm
341 Mm
341 mm
370 mm
185.8 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Net weight	13.3 kg
[lth] conventional free air thermal current	200 A at 60 °C

Environment

Standards	IEC 60947-6-1	
Product certifications	CE[RETURN]CB[RETURN]CCC	
IP degree of protection	Front face: IP40 running Inside the enclosure: IP20 manual mode	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Pollution degree	3	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	73.000 cm	
Package 1 Width	60.000 cm	
Package 1 Length	80.000 cm	
Package 1 Weight	27.499 kg	

Offer Sustainability

oner odetamasmity		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

