



Main

Range of product	TransferPacT
Product or component type	Remote transfer switch
Device application	Change source of supply
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
Downside connection	Screwed
Mounting mode	Fixed
Upside connection	Screwed
Contact position indicator	Yes
[Icm] rated short-circuit making capacity	40 kA switch-disconnector alone 230 V AC at 50 Hz 330 kA with upstream protection circuit breaker 230 V AC at 50 Hz
Suitability for isolation	Yes

Complementary

Transfer switch class	PC
Number of contact position	3
Signal contacts composition	1 NO + 2 NC 1 NC + 2 NO 2 NO
Utilization category	AC-33B
[Ue] rated operational voltage	230 V AC 50/60 Hz
Control type	Remote control
Operating mode	Manual Remote
Display type	Alarm indicator
Mounting support	Plate
Locking options description	Padlock in OFF position Padlock in SI / SII position
Rated duty	Uninterrupted
[Ui] rated insulation voltage	Switch: 800 V Controller: 500 V
[Uimp] rated impulse withstand voltage	Switch: 8 kV Controller: 6 kV
[Ie] rated operational current	630 A
Mechanical interlocking	With mechanical interlocking
Mechanical durability	10000 cycles
Connection pitch	35 mm
Local signalling	LED indicator (green) for power ON LED indicator (red) for alarm
[Icw] rated short-time withstand current	20 kA during 0.5 s 25 kA during 0.1 s
Height	341 mm
Width	467 mm
Depth	186 mm

Net weight	20.8 kg
[Ith] conventional free air thermal current	630 A at 60 °C

Environment

Standards	IEC 60947-6-1
Product certifications	CE[RETURN]CB[RETURN]CCC
IP degree of protection	Front face: IP40 running Inside the enclosure: IP20 manual mode
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	73.000 cm
Package 1 Width	60.000 cm
Package 1 Length	80.000 cm
Package 1 Weight	35.900 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information