



Main

Net weight	340 g
Product or component type	Communication card
Ambient air temperature for storage	-30...50 °C
Ambient air temperature for operation	0...50 °C
Communication port protocol	Zigbee Pro
Standards	FCC part 15 Subpart C
Storage Relative Humidity	0...95 % non-condensing
Relative humidity	0...95 %
Range	EcoStruxure Building Expert

Complementary

Accessory / separate part category	Communication accessory
------------------------------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	7.5 cm
Package 1 Length	12.2 cm
Package 1 Weight	31 g

Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.