

## VF208W-125NZ

VF208W Butterfly Valve, 2-Way, DN125, Wafer Flanged, Zinc Plated Disc, EPDM Liner, Kvs 1025 m<sup>3</sup>/h, Max  $\Delta P$  600 kPa.



### Main

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Product or component type              | Valve                                              |
| Valve type                             | Butterfly                                          |
| Valve product series                   | VF208W                                             |
| Valve model                            | VF208W 125NZ 1025E B00                             |
| Medium compatibility                   | Glycol 25 %<br>Glycol 30 %<br>Glycol 50 %<br>Water |
| Valve configuration                    | 2-Way                                              |
| Valve connection type                  | Flanged                                            |
| Body size                              | 125 mm (5 in)                                      |
| Pipe size                              | 125 mm                                             |
| Flow characteristic                    | Uncharacterized                                    |
| Flow coefficient                       | 1185.13 cv<br>1025 kvs                             |
| Pressure class                         | PN16                                               |
| Operating fluid temperature            | -10...100 °C                                       |
| Pressure fluid max delta P normal life | 303.37 kPa                                         |
| Seat leakage                           | Port A: Class IV-S1 (0.005 %)                      |
| Stem movement                          | Rotary                                             |
| Disc shape                             | Full                                               |
| Disc material                          | Nodular cast iron                                  |
| Body material                          | Nodular cast iron EN-JS 1030                       |
| Material seal                          | EPDM (ethylene propylene diene monomer)            |
| Stem material                          | Stainless steel AISI 420                           |
| Targeted region                        | Europe<br>Asia Pacific.<br>Australia.              |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 8.89 cm  |
| Package 1 Width              | 26.67 cm |
| Package 1 Length             | 19.05 cm |
| Package 1 Weight             | 6.55 kg  |

### Offer Sustainability

|                          |                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive        | Not applicable, out of EU RoHS legal scope                                                                                        |
| Environmental Disclosure |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | No need of specific recycling operations                                                                                          |