



Main

Product or component type	Valve
Valve type	Globe
Valve product series	VG221F
Valve model	VG221F-125C 200M SU00
Medium compatibility	Water Glycol 25 % Glycol 30 % Glycol 50 %
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN125 (ISO 7005-2)
Body size	125 mm (5 in)
Pipe size	125 mm
Flow characteristic	Equal percentage
Flow coefficient	231.25 cv 200.01 kvs
Pressure class	PN16
Operating fluid temperature	-10... 150 °C
Pressure fluid max delta P normal life	199.95 kPa
Control valve rangeability	Greater than 50:1
Stroke length	45 mm
Seat leakage	Port A: Less than 0.03 % of kvs
Stem flow action	Stem up closed
Stem movement	Linear
Trim material	Brass
Body material	Grey cast iron GG-25
Seat material	Port A: grey cast iron GG-25
Stem material	Stainless steel AISI 303
Plug material	CW614N brass
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.0 cm
Package 1 Width	25.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	45.0 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information