

Product data sheet

Characteristics

VG311F-65C

VG311F Globe Valve, 3-Way, DN65, Flanged, Kvs 63 m³/h, Cast Iron Body and Seat, Brass Plug.



Main

Product or component type	Valve
Valve type	Globe
Valve product series	VG311F
Valve model	VG311F-65C 63M SU00
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	Flanged
Valve connection size	DN65 (ISO 7005-2)
Body size	65 mm (2-1/2 in)
Pipe size	65 mm
Flow characteristic	Equal percentage
Flow coefficient	75.15 cv 63 kvs
Pressure class	PN16
Operating fluid temperature	-10...150 °C
Pressure fluid max delta P normal life	199.95 kPa
Control valve rangeability	Greater than 50:1
Stroke length	25 mm
Seat leakage	Port A: Less than 0.03 % of kvs
Stem flow action	Stem up closes A and opens B to AB
Stem movement	Linear
Trim material	Brass
Body material	Grey cast iron GG-25
Seat material	Port A: grey cast iron GG-25 Port B: grey cast iron GG-25
Stem material	Stainless steel AISI 303
Plug material	CW614N brass
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A: metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	18.5 cm
Package 1 Length	29.0 cm
Package 1 Weight	18.0 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or intended user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information