

VP228E-15BQS

SpaceLogic VP228E PIBCV (PICV), 2-Way,
PN16, DN15, G3/4 Ext. Thread, Std Flow:
0.09...0.45 m³/h (0.025...0.13 l/s).

Main

Valve product range	SpaceLogic
Product or component type	Valve
Valve type	Pressure independent
Valve product series	VP228E
Device application	Fan coil unit Radiation panel Terminal unit
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	G External
Valve connection size	G 3/4A
Body size	15 mm (1/2 in)
Pipe size	15 mm
Flow characteristic	Linear
Pressure allowable static	16 bar, 200 psi up to 150 °F
Pressure class	PN16 ANSI class 125
Operating fluid temperature	-10...120 °C
Pressure fluid max delta P normal life	399.90 kPa
Flow rate minimum (gpm)	0.4 gal(US)/min
Flow rate nominal (gpm)	2 gal(US)/min
Flow rate maximum (gpm)	2.4 gal(US)/min
Flow rate minimum (lps)	0.025 l/s
Flow rate nominal (lps)	0.13 l/s
Flow rate nominal (m³/h)	0.45 m³/h
Flow rate maximum (lps)	0.15 l/s
Flow rate minimum (m³/h)	0.09 m³/h
Flow rate maximum (m³/h)	0.54 m³/h
Pressure differential minimum (kPa)	16 kPa
Pressure differential maximum (kPa)	600 kPa
Pressure differential minimum (psi)	2.32 psi 2.32 psi
Pressure differential maximum (psi)	87 psi 87 psi
Close-off pressure	232 psi 1600 kPa
Control valve rangeability	1000:1
Stroke length	2.25 mm
Seat leakage	Port A: Class IV (0.01 %)
Accuracy setting knob	5 %
Stem movement	Linear
Body material	CW602N brass
Seat material	Port A: brass
Stem material	Stainless steel

Stem seal material	EPDM (ethylene propylene diene monomer)
Material diaphragm	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. North America. Australia.

Complementary

Flow rate maximum (lph)	540 l/h
Flow rate minimum (lph)	90 l/h
Flow rate nominal (lph)	450 l/h

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.9 cm
Package 1 Width	9.3 cm
Package 1 Length	9.3 cm
Package 1 Weight	480.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	4
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.281 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes