

Product data sheet

Characteristics

VT2337

Erie Zone Valve, 2-Way, PN16, DN20 (3/4"), Rp Thread, Kvs 6.5 m³/h (Cv 7.5), Pop-Top Actuator Connection, Brass Body.



Main

Valve product range	Erie PopTop
Product or component type	Valve
Valve type	Zone
Valve product series	VT2
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Rp Internal
Body size	20 mm (3/4 in)
Pipe size	DN20
Flow characteristic	Uncharacterized
Flow coefficient	7.5 cv 6.49 kvs
Pressure allowable static	300 psi
Pressure class	PN16 PN20
Operating fluid temperature	0...93 °C
Pressure fluid max delta P normal life	137.90 kPa
Seat leakage	Port A: Class IV (0.01 %)
Stem movement	Rotary
Trim material	Brass
Body material	Brass
Seat material	Port A: brass
Paddle material	Buna N
Stem material	Nickel plated brass
Stem seal material	FKM
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.08 cm
Package 1 Width	7.62 cm
Package 1 Length	7.62 cm
Package 1 Weight	410.0 g

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	 Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.