

VT2437

Erie Zone Valve, 2-Way, PN16, DN25 (1"),
Rp Thread, Kvs 6.9 m³/h (Cv 8.0), Pop-Top
Actuator Connection, Brass Body.



Main

Valve product range	Erie PopTop
Product or component type	Valve
Valve type	Zone
Valve product series	VT2
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Rp Internal
Body size	25 mm (1 in)
Pipe size	DN25
Flow characteristic	Uncharacterized
Flow coefficient	8 cv 6.92 kvs
Pressure allowable static	300 psi
Pressure class	PN16 PN20
Operating fluid temperature	0...93 °C
Pressure fluid max delta P normal life	137.90 kPa
Seat leakage	Port A: Class IV (0.01 %)
Stem movement	Rotary
Trim material	Brass
Body material	Brass
Seat material	Port A: brass
Paddle material	Buna N
Stem material	Nickel plated brass
Stem seal material	FKM
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.4 cm
Package 1 Width	12.0 cm
Package 1 Length	14.0 cm
Package 1 Weight	571.6 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile