

# Product data sheet

## Characteristics

# VT3232

Erie Zone Valve, 3-Way, PN16, DN15 (1/2"), Rp Thread, Kvs 2.6 m<sup>3</sup>/h (Cv 3.0), Pop-Top Actuator Connection, Brass Body.



### Main

Valve product range	Erie PopTop
Product or component type	Valve
Valve type	Zone
Valve product series	VT3
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	Rp Internal
Body size	15 mm (1/2 in)
Pipe size	DN15
Flow characteristic	Uncharacterized
Flow coefficient	2.5 cv 2.16 kvs
Pressure allowable static	300 psi
Pressure class	PN16 PN20
Operating fluid temperature	0...93 °C
Pressure fluid max delta P normal life	344.74 kPa
Seat leakage	Port A: Class IV (0.01 %)
Stem movement	Rotary
Trim material	Brass
Body material	Brass
Seat material	Port A: brass
Paddle material	Buna N
Stem material	Nickel plated brass
Stem seal material	FKM
Targeted region	Europe Asia Pacific. Australia.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.08 cm
Package 1 Width	7.62 cm
Package 1 Length	7.62 cm
Package 1 Weight	410.0 g

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>