



Main

Range of product	PacDrive 3
Product or component type	Cable

Complementary

Range compatibility	Lexium 62
Product compatibility	LXM 62 connection module LXM 62 distribution box
Type of cable	Shielded motor cable
Connector type	RJ45 D2 ,elbowed shape
Accessory / separate part destination	24 V DC bus Connector for safe torque off safety function signals
Cable length	14 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.4 cm
Package 1 Width	44.1 cm
Package 1 Length	44.1 cm
Package 1 Weight	5.091 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.