VW3L40020

insert - 1 female/male M8, 4 pins- for 2 signals safe torque off safety function

Main

Range of product	Lexium integrated drive
Product or component type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

Complementary

Electrical connection	1 female connector M8 4 pins for for connection of signals for safe torque off 1 male connector M8 4 pins for for connection of signals for safe torque off
Kit composition	1 sealing insert 1 insert with connectors
Input/output type	2 STO signals
Net weight	0.027 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	4.0 cm
Package 1 Length	6.0 cm
Package 1 Weight	28.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.432 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months