

Product data sheet

Characteristics

VW3L40420

insert - 4 female M8 for 2 I/O signals + 2 male M8 for safe torque off safety



Main

Range of product	Lexium integrated drive
Product or component type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

Complementary

Electrical connection	1 female connector M8 4 pins for for connection of signals for safe torque off 1 male connector M8 4 pins for for connection of signals for safe torque off 4 female connectors M8 3 pins for for connection of 4 I/O signals
Kit composition	2 inserts with 3 connectors
Input/output type	4 I/O signals + 2 STO signals
Net weight	0.054 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	5.000 cm
Package 1 Length	10.000 cm
Package 1 Weight	54.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	25
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.520 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty

18 months
