



Main

Range compatibility	Lexium 32
Accessory / separate part category	Communication accessories
Accessory / separate part type	Module
Product or component type	Additional I/O module
Product compatibility	Lexium 32M
Accessory / separate part destination	Servo drive

Complementary

Input/output type	4 discrete inputs: - 3...5 V/15...30 V, 2.5 mA, for 0.25 ms 2 discrete outputs: ≤ 30 V, ≤ 100 mA, for 0.25 ms 2 analog outputs: - 10...10 V, 0...20 mA, 470 Ohm, resolution: 12 bits for 0.25 ms 2 analog inputs: - 10...10 V, 20 kOhm, resolution: 14 bits for 0.25 ms
Protection type	Reverse polarity protection on input
Reverse polarity protection	Yes on input
Short-circuit protection	Yes on output
Electrical connection	Spring terminal
Net weight	0.45 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	13.0 cm
Package 1 Length	19.0 cm
Package 1 Weight	134.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	4.044 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Contractual warranty	
Warranty	18 months