

Product data sheet

Characteristics

VW3M5104R100

power cable- between servomotor BSH and servodrive - 4 x 10 mm² + 2 x 1 mm² -10m



Main

Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BMH, 2 motor stacks (190 mm) mounting type B2 conforming to EN 60204-1 Servo motor BMH, 3 motor stacks (190 mm) mounting type B2 conforming to EN 60204-1
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 32
Cable length	10 m
Cable composition	4 x 10 mm ² + 2 x 1 mm ²

Complementary

Electrical connection	Free end for servo drive side Connector - industrial M40 for servo motor side
Net weight	10.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	60.0 cm
Package 1 Length	60.0 cm
Package 1 Weight	9.1 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.