



Main

Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BMH, 1 motor stacks (190 mm) mounting type B2 conforming to IEC 60204-1 Servo motor BMH, 2 motor stacks (190 mm) mounting type E conforming to IEC 60204-1 Servo motor BMH, 3 motor stacks (190 mm) mounting type E conforming to IEC 60204-1 Servo motor BMH, 3 motor stacks (205 mm) mounting type B2 conforming to IEC 60204-1
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 32
Cable length	15 m
Cable composition	4 x 6 mm ² + 2 x 1 mm ²

Complementary

Electrical connection	Free end for servo drive side Connector - industrial M40 for servo motor side
Net weight	9.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.16 cm
Package 1 Width	44.45 cm
Package 1 Length	46.99 cm
Package 1 Weight	9.489 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------