

Product data sheet

Characteristics

VW3M5D2FR50

power cable 5m shielded 4x 1,3mm², BCH2
brake MIL connector



Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 at 1000 W (100 mm) (with brake) Servo motor BCH2 at 2000 W (100 mm) (with brake) Servo motor BCH2 at 300 W (130 mm) (with brake) Servo motor BCH2 at 500 W (130 mm) (with brake) Servo motor BCH2 at 600 W (130 mm) (with brake) Servo motor BCH2 at 850 W (130 mm) (with brake) Servo motor BCH2 at 900 W (130 mm) (with brake) Servo motor BCH2 at 1000 W (130 mm) (with brake) Servo motor BCH2 at 1500 W (130 mm) (with brake) Servo motor BCH2 at 2000 W (130 mm) (with brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	5 m

Complementary

Electrical connection	Free end for servo drive side Connector - MIL small for servo motor side
AWG gauge	6 x AWG 16
Net weight	0.9 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	31.0 cm
Package 1 Length	37.0 cm
Package 1 Weight	1.08 kg
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.483 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration

RoHS exemption information

Yes

PVC free

Yes
