

# Product data sheet

## Characteristics

# VW3S5101R150

power cable 4x1.5mm<sup>2</sup>, Lexium SD3,  
between stepper drive SD3 and 3 phases  
motor, shielded, 15m



### Main

Accessory / separate part designation	Power cable
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD3 and 3-phase stepper motor
Range compatibility	Lexium SD3
Type of cable	Shielded cable
Cable length	15 m

### Complementary

Cable composition	4 x 1.5 mm <sup>2</sup>
Electrical connection	1 connector 6-pole circular (motor end) Cable end open (SD3)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	30.0 cm
Package 1 Length	31.0 cm
Package 1 Weight	2.626 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	11.756 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

Circularity Profile

 End Of Life Information

---

PVC free

Yes

---

**Contractual warranty**

---

Warranty

18 months

---