

Product data sheet

Characteristics

VW3S8201R50

cable for pulse/direction signal, Lexium SD3,
5V, shielded, 5m



Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and external impulsion generator
Range compatibility	Lexium SD3
Type of cable	Shielded cable
Cable length	5 m

Complementary

Product compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex (SD326) Cable end open (external impulsion generator)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	26.0 cm
Package 1 Length	28.0 cm
Package 1 Weight	464.0 g
Unit Type of Package 2	S06
Number of Units in Package 2	60
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	40.84 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------