

# Product data sheet

## Characteristics

# VW3S8202R50

## cable for pulse/direction signal, Lexium SD3, 24V, shielded, 5m



### Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and external impulsion generator
Range compatibility	Lexium SD3
Type of cable	Shielded cable
Cable length	5 m

### Complementary

Product compatibility	SD326
[Uc] control circuit voltage	24 V
Electrical connection	1 connector 24-pole Molex (SD326) Cable end open (external impulsion generator)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	26.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	466.0 g
Unit Type of Package 2	S06
Number of Units in Package 2	60
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	40.96 kg

### Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------