

# Product data sheet

## Characteristics

# VW3S8206R30

## cable for pulse/direction signal, Lexium SD3, 24V, 3m



### Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and Siemens programmable controller S7-300 FM353
Range compatibility	Lexium SD3
Cable length	3 m

### Complementary

Product compatibility	SD326
[Uc] control circuit voltage	24 V
Electrical connection	1 connector 24-pole Molex (SD326) 1 connector SUB-D 15 (S7-300 FM353)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	40 cm
Package 1 Length	30 cm
Package 1 Weight	439 g
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Height	3 cm
Package 2 Width	40 cm
Package 2 Length	30 cm
Package 2 Weight	939 g

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	Yes
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------