## Product data sheet Characteristics

## XACV07

# incandescent bulb - multi-button - front mounted - 230 V



#### Main

Electrical circuit type Control circuit

Complementary

Control station category  Enclosure material  Glass reinforced polyester Metal  Light source  Bulb included  Mounting of block  Front mounted  0.055 kg  [Ue] rated operational voltage  130 V  Supply  Direct through resistor			
Enclosure material  Glass reinforced polyester Metal  Light source  Bulb included  Mounting of block  Front mounted  0.055 kg  [Ue] rated operational voltage  130 V  Supply  Direct through resistor	Bulb type	Incandescent	
Light source Bulb included  Mounting of block Front mounted  Net weight 0.055 kg  [Ue] rated operational voltage 130 V  Supply Direct through resistor	Control station category	Multi-button	
Mounting of block Front mounted  Net weight 0.055 kg  [Ue] rated operational voltage 130 V  Supply Direct through resistor	Enclosure material	• •	
Net weight 0.055 kg  [Ue] rated operational voltage 130 V  Supply Direct through resistor	Light source	Bulb included	
[Ue] rated operational voltage 130 V Supply Direct through resistor	Mounting of block	Front mounted	
Supply Direct through resistor	Net weight	0.055 kg	
	[Ue] rated operational voltage	130 V	
[Us] rated supply voltage 230 V	Supply	Direct through resistor	
	[Us] rated supply voltage	230 V	

#### **Packing Units**

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	6.000 cm
Package 1 Length	7.500 cm
Package 1 Weight	71.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.612 kg

### Offer Sustainability

REACh Declaration	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope)	
Yes	
Yes	

China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Contractual warranty		
Warranty	18 months	