XARSK12D18W

Harmony eXLhoist. standard. XARS12D18W system with charger. shoulder belt. cable USB/RJ45 and config software



Main Range of product Harmony eXLhoist Product or component Control station type XARS Device short name Control station type Wireless Product specific Hoisting applications application Material handling Number of channels Stop function: SIL 2 maximum (can reach PL d/ Control station application category 3) conforming to IEC 62061 Stop function: SIL 2 maximum (can reach PL d/ category 3) conforming to ISO 13849-1 Emergency stop function: SIL 3 maximum (can reach PL e/category 4) conforming to IEC 62061

Emergency stop function: SIL 3 maximum (can reach PL e/category 4) conforming to IEC 62061 Emergency stop function: SIL 3 maximum (can reach PL e/category 4) conforming to ISO 13849-1 Motion function: SIL 1 maximum (can reach PL c/category 1) conforming to IEC 62061 Motion function: SIL 1 maximum (can reach PL c/category 1) conforming to ISO 13849-1 Limiter protection function: SIL 1 maximum (can reach PL c/category 1) conforming to IEC 62061 Limiter protection function: SIL 1 maximum (can reach PL c/category 1) conforming to ISO 13849-1

Complementary

Kit composition	Base station	
·	Configuration software	
	Cable	
	Remote control	
	Shoulder belt	
Operating distance	100 m in free air	
Cable entry	Cable gland	
Communication network type	Wireless: bluetooth low energy	
Transmission frequency	2.4 GHz	

Environment

Radio agreement	ARIB
	SRRC
	RSS
	ANATEL
	FCC
	ICASA
Relative humidity	095 % at -2045 °C storage
Electromagnetic compatibility	Resistance to electrostatic discharge - test level: 4 kV class B (on contact) conforming to IEC 61000-4-2
	Resistance to electrostatic discharge - test level: 8 kV class B (in air) conforming to IEC 61000-4-2
	Resistance to radiated electromagnetic fields - test level: 10 V/m class B conforming to IEC 61000-4-3
Standards	IEC 60204-1 safety
	ISO 13849-1 safety
	IEC 62061 safety
	IEC 61508 safety
	ISO 13850 safety
	IEC 60204-32 hoisting applications
	ETSI EN 301 489-1 radio
	ETSI EN 301 489-3 radio
	ETSI EN 301 489-17 radio
	ETSI EN 300 440-2 radio
	ETSI EN 300 328 radio
	FCC part 15 radio
	RSS GEN issue 3 radio
	RSS 210 issue 8 radio
	ARIB STD-T81 radio
Product certifications	CE[RETURN]UL[RETURN]CSA[RETURN]C-
	Tick[RETURN]JIS[RETURN]KC[RETURN]EAC

Packing Units

5	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.000 cm
Package 1 Width	29.000 cm
Package 1 Length	31.000 cm
Package 1 Weight	3.042 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	6.820 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	