XD2AL201

Complete joystick controller, XD2, XD4, 30mm, 2 directions, 1 CO per direction





Main

| Range of product | Harmony XD2 |
|---------------------------|------------------------------|
| Product or component type | Complete joystick controller |
| Device short name | XD2 |
| Mounting diameter | 30 mm |
| Bezel material | Chromium plated metal |
| | |

Complementary

| Complementary | |
|--------------------------------|--|
| Operator position information | All positions |
| Notch per direction | 1 |
| Operator direction information | 2 directions |
| Contacts type and composition | 1 C/O for snap action |
| Short-circuit protection | 10 A gG (gl) Neozed cartridge fuse conforming to IEC 60947-5-1 |
| Connections - terminals | Captive screw clamp terminals, $2 \times 1.5 \text{ mm}^2$ with or without cable end Captive screw clamp terminals, $1 \times 2.5 \text{ mm}^2$ with or without cable end |
| Electrical durability | 1000000 Cycles, AC-15 at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 Cycles, AC-15 at 127 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 at 48 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 1000000 cycles, AC-15 at 48 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Contact code designation | A600-Q600 |
| Overvoltage category | Class I conforming to IEC 61140 |
| Mechanical durability | 1000000 cycles |
| Fixing center | 60 x 100 mm |
| Return | without |
| Height | 161 mm |
| Depth | 68 mm |
| Net weight | 0.23 kg |
| | |

Environment

| Liviloriment | | |
|---------------------------------------|---|--|
| Standards | IEC 60947-5-1 | |
| Product certifications | CSA | |
| Protective treatment | TC | |
| Ambient air temperature for storage | -4070 °C | |
| Ambient air temperature for operation | -2570 °C | |
| Vibration resistance | 25 gn (f= 10500 Hz) conforming to IEC 60068-2-6 | |
| Shock resistance | 50 gn conforming to IEC 60068-2-27 | |
| IP degree of protection | IP40 conforming to IEC 60529 | |

Packing Units

| 3 | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.500 cm |
| Package 1 Width | 8.500 cm |
| Package 1 Length | 17.500 cm |
| Package 1 Weight | 273.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 1.930 kg |
| | |

Offer Sustainability

| Pro-active compliance (Product out of EU RoHS legal scope) |
|---|
| Pro-active compliance (Product out of EU RoHS legal scope) |
| |
| · · |
| Yes |
| China RoHS Declaration |
| ₽¥Yes |
| Product Environmental Profile |
| No need of specific recycling operations |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| |