

# XVUC65

Modular tower light, Harmony XVU, illuminated LED units, orange, 60mm, high flashing, IP65, 24V AC DC



## Main

Range of product	Harmony XVU
Product or component type	Modular tower light
Beacon or indicator bank unit type	LED unit
Mounting diameter	60 mm
Component name	XVU
Light source	LED, orange
Device application	Automotive Packaging machine Machine tools

## Complementary

Signalling type	High flashing
Assembly style	Customer assembly, up to 3 units
Material	PC (polycarbonate) V-2 conforming to UL 94
[Us] rated supply voltage	24 V AC/DC
Maximum power dissipation in W	2.9 W
Current consumption	<= 150 mA
Signalling type	High flashing
Length	60 mm
Net weight	0.085 kg






## Environment

Product certifications	UL[RETURN]CSA[RETURN]CE[RETURN]EAC[RETURN]RCM
Ambient air temperature for storage	-40...70 °C
IP degree of protection	IP65
Ambient air temperature for operation	-25...50 °C
Vibration resistance	2 gn

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	9.5 cm
Package 1 Length	13.4 cm
Package 1 Weight	164.0 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
RoHS exemption information	<a href="#"> Yes</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>
Circularity Profile	<a href="#"> End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

## Illuminated LED Unit

---

### Dimensions

mm  
in.

