



## Main

Range of product	Harmony XAC
Product or component type	Head for emergency switching off push-button
Sale per indivisible quantity	1

## Complementary

Product compatibility	XACA..
Mounting location	Front of enclosure
Overvoltage category	Class II conforming to IEC 61140
Operator profile	Red mushroom Ø 40 mm
Net weight	0.065 kg
Marking	Unmarked

## Environment

Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
IK degree of protection	IK08
Standards	UL 508 CSA C22.2 No 14 IEC 60947-5-5 IEC 60947-5-1 IEC 60204-32 IEC 62262
Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	4.000 cm
Package 1 Length	9.000 cm
Package 1 Weight	73.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	10.000 cm
Package 2 Width	13.000 cm
Package 2 Length	16.000 cm
Package 2 Weight	746.000 g
Unit Type of Package 3	S01
Number of Units in Package 3	40

Package 3 Height	15.000 cm
Package 3 Width	15.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.122 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>