



### Main

|                               |                              |
|-------------------------------|------------------------------|
| Range of product              | Harmony XB4                  |
| Product or component type     | Head for key selector switch |
| Device short name             | ZB4                          |
| Bezel material                | Chromium plated metal        |
| Mounting diameter             | 22 mm                        |
| Head type                     | Standard                     |
| Sale per indivisible quantity | 1                            |
| Shape of signaling unit head  | Round                        |
| Operator profile              | Black key switch             |
| Type of operator              | Stay put                     |
| Operator position information | 2 positions 90°              |
| Type of keylock               | CES TEC10                    |
| Key withdrawal position       | Left                         |

### Complementary

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                  | 29 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| CAD overall height                 | 29 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| CAD overall depth                  | 72 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Net weight                         | 0.16 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance : 0.1 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Mechanical durability              | 1000000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Electrical composition code        | C3 for <6 contacts using single blocks in front mounting<br>C4 for <6 contacts using single and double blocks in front mounting<br>C5 for <5 contacts using single blocks in front mounting<br>C6 for <5 contacts using single and double blocks in front mounting<br>C7 for <4 contacts using single blocks in front mounting<br>C8 for <4 contacts using single and double blocks in front mounting<br>C11 for <3 contacts using single blocks in front mounting<br>C15 for <1 contacts using single blocks in front mounting |
| Device presentation                | Basic element                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### Environment

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| Protective treatment                  | TH                                                    |
| Ambient air temperature for storage   | -40...70 °C                                           |
| Ambient air temperature for operation | -40...70 °C                                           |
| Overvoltage category                  | Class I conforming to IEC 60536                       |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67<br>IP69<br>IP69K |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                    |
| IK degree of protection               | IK06 with keyhole cover ZBGP conforming to IEC 50102  |

|                        |                                                                                                                                                                                |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards              | EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>GB 14048.5<br>EN/IEC 60947-5-5<br>UL 508<br>CSA C22.2 No 14                                                          |
| Product certifications | CSA[RETURN]DNV[RETURN]BV[RETURN]UL listed[RETURN]LROS (Lloyds register of shipping)[RETURN]GL                                                                                  |
| Vibration resistance   | 5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                                                               |
| Shock resistance       | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 3.300 cm  |
| Package 1 Width              | 5.300 cm  |
| Package 1 Length             | 9.000 cm  |
| Package 1 Weight             | 164.000 g |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| REACH Regulation           |  <a href="#">REACH Declaration</a>               |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)                                                                        |
| Mercury free               | Yes                                                                                                                               |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---



Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board                                                                                                                                                                                                                | Connection by Faston Connectors |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
|                                                                                                                                                                                                                                                                                                      |                                 |
| (1) Diameter on finished panel or support<br>(2) 40 mm min. / 1.57 in. min.<br>(3) 30 mm min. / 1.18 in. min.<br>(4) $\varnothing$ 22.5 mm / 0.89 in. recommended ( $\varnothing$ 22.3 mm $_0^{+0.4}$ / 0.88 in. $_0^{+0.016}$ )<br>(5) 45 mm min. / 1.78 in. min.<br>(6) 32 mm min. / 1.26 in. min. |                                 |

Pushbuttons, Switches and Pilot Lights for Printed Circuit Board Connection

Panel Cut-outs (Viewed from Installer's Side)



A: 30 mm min. / 1.18 in. min.  
 B: 40 mm min. / 1.57 in. min.

Printed Circuit Board Cut-outs (Viewed from Electrical Block Side)

Dimensions in mm



A: 30 mm min.  
B: 40 mm min.  
Dimensions in in.



A: 1.18 in. min.  
B: 1.57 in. min.

### General Tolerances of the Panel and Printed Circuit Board

The cumulative tolerance must not exceed 0.3 mm / 0.012 in:  $T1 + T2 = 0.3 \text{ mm max.}$

## Installation Precautions

- Minimum thickness of circuit board: 1.6 mm / 0.06 in.
- Cut-out diameter: 22.4 mm  $\pm$  0.1 / 0.88 in.  $\pm$  0.004
- Orientation of body/fixing collar ZB4 BZ009:  $\pm 2^\circ 30'$  (excluding cut-outs marked a and b).
- Tightening torque of screws ZBZ 006: 0.6 N.m (5.3 lbf.in) max.
- Allow for one ZB4 BZ079 fixing collar/pillar and its fixing screws:
  - every 90 mm / 3.54 in. horizontally (X), and 120 mm / 4.72 in. vertically (Y).
  - with each selector switch head (ZB4 BD•, ZB4 BJ•, ZB4 BG•).

The fixing centers marked a and b are diagonally opposed and must align with those marked 4 and 5.



(1) Panel

(2) Printed circuit board

## Mounting of Adapter (Socket) ZBZ 01•


- 1 2 elongated holes for ZBZ 006 screw access
- 2 1 hole  $\varnothing$  2.4 mm  $\pm$  0.05 / 0.09 in.  $\pm$  0.002 for centring adapter ZBZ 01•
- 3 8  $\times$   $\varnothing$  1.2 mm / 0.05 in. holes
- 4 1 hole  $\varnothing$  2.9 mm  $\pm$  0.05 / 0.11 in.  $\pm$  0.002, for aligning the printed circuit board (with cut-out marked a)
- 5 1 elongated hole for aligning the printed circuit board (with cut-out marked b)
- 6 4 holes  $\varnothing$  2.4 mm / 0.09 in. for clipping in adapter ZBZ 01•

Dimensions An + 18.1 relate to the  $\varnothing$  2.4 mm  $\pm$  0.05 / 0.09 in.  $\pm$  0.002 holes for centring adapter ZBZ 01•.

---

Electrical Composition Corresponding to Code C3

---



---


Electrical Composition Corresponding to Code C4

---

---

Electrical Composition Corresponding to Code C5

---



---

Electrical Composition Corresponding to Code C6

---

---

Electrical Composition Corresponding to Code C7

---

## Electrical Composition Corresponding to Code C8

---

## Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1

---

## Electrical Composition Corresponding to Code C15

---

1 N/O

1 N/C

1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C

## Legend

---

Single contact

Double contact

Light block

Possible location



## Sequence of Contacts Fitted to 2-position Selector Switch Body

### Position 315°



|          |                                                                                     |                                                                                     |                                                                                     |        |      |
|----------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------|------|
| Push     | Position                                                                            | Top                                                                                 |                                                                                     |        |      |
| Bottom   |  |  |  |        |      |
| Location |                                                                                     | Left                                                                                | Centre                                                                              | Right  |      |
| State    |                                                                                     | 0                                                                                   | 0                                                                                   | 0      |      |
| Contacts | N/O                                                                                 |                                                                                     | open                                                                                | open   | open |
| N/C      |                                                                                     | closed                                                                              | closed                                                                              | closed |      |

### Position 45°



|          |                                                                                     |      |        |        |        |
|----------|-------------------------------------------------------------------------------------|------|--------|--------|--------|
| Push     | Position                                                                            | Top  |        |        |        |
| Bottom   |  |      |        |        |        |
| Location |                                                                                     | Left | Centre | Right  |        |
| State    |                                                                                     | 1    | 1      | 1      |        |
| Contacts | N/O                                                                                 |      | closed | closed | closed |
| N/C      |                                                                                     | open | open   | open   |        |