ZD5PA24

Head for joystick controller, Harmony XB5, XDA, plastic, 22 mm, 4 directions, spring return, 1NO



Main

| Range of product | Harmony XB5 |
|--------------------------------|--------------------------------|
| Product or component type | Head for joystick controller |
| Device short name | ZD5 |
| Bezel material | Plastic |
| Mounting diameter | 22 mm |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Type of operator | To zero position spring return |
| Operator profile | 54 mm long operating shaft |
| Operator direction information | 4 directions |
| | |

Complementary

| CAD overall width | 30 mm | |
|------------------------------------|---------------------------------------|--|
| CAD overall height | 47 mm | |
| CAD overall depth | 85 mm | |
| Net weight | 0.022 kg | |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance : 0.1 m | |
| Mechanical durability | 1000000 cycles | |
| Device presentation | Basic element | |

Environment

| Protective treatment | ТН |
|---------------------------------------|---|
| Ambient air temperature for storage | -4070 °C |
| Ambient air temperature for operation | -2570 °C |
| Electrical shock protection class | Class II conforming to IEC 60536 |
| IP degree of protection | IP66 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| IK degree of protection | IK03 conforming to IEC 50102 |
| Standards | JIS C8201-5-1 UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-1 JIS C8201-1 |
| Product certifications | UL listed[RETURN]GL[RETURN]BV[RETURN]CSA[RETURN]LROS (Lloyds register of shipping)[RETURN]DNV |
| Vibration resistance | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

Packing Units

| 3 | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.2 cm |
| Package 1 Width | 3.4 cm |
| Package 1 Length | 8.8 cm |
| Package 1 Weight | 35.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 2.205 kg |
| | |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|----------------------------|---|
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | €Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| | |