

Product data sheet

Characteristics

DA1TS100

PTC thermistor probe DA1-T - surface probe - 100°C



Main

Range of product	DA1
Product or component type	Thermistor probe
Device short name	DA1TS
Accessory / separate part category	Protection accessory
Quantity per set	Set of 10
Ambient air temperature for operation	100 °C

Complementary

[Ui] rated insulation voltage	1000 V
[Ue] rated operational voltage	<= 2.5 V
Resistance	250 Ohm per probe 25 °C
Insulation	Reinforced
Cable length	1 m between probe and motor terminal plate
Net weight	0.005 kg

Environment

Standards	IEC 60034-11 Mark A
-----------	---------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8 g
Package 1 Height	1.5 cm
Package 1 width	9.5 cm
Package 1 Length	11.5 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	86 g
Package 2 Height	10 cm
Package 2 width	2 cm
Package 2 Length	12 cm
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Weight	1.02 kg
Package 3 Height	15 cm
Package 3 width	15 cm
Package 3 Length	40 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------