



Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard Network Interface Module
Integrated connection type	Fipio conforming to EN 50170, vol3, part 1-3, 2-3, 3-3, 5-3, 6-3,7-3 9-way male SUB-D connector 1 twisted shielded pair (bus) Fipio conforming to EN 50170, vol3, part 1-3, 2-3, 3-3, 5-3, 6-3,7-3 HE-13 (RS232 port) Fipio conforming to EN 50170, vol3, part 1-3, 2-3, 3-3, 5-3, 6-3,7-3 8-way female (RS232 port)
Number of segments	1 primary, maximum 6 extensions
Number of devices per segment	0...128 all segment 0...32 per segment
Transmission rate	1 Mbit/s for bus length of 0...1000 m per segment
Structure type	Open industrial fieldbus

Complementary

Number of addressable I/O module	0...32 per island
Communication service	FSD FDR FED Periodic I/O exchanges Point to point message
[Us] rated supply voltage	24 V DC
Power supply type	SELV
Maximum supply current	700 A
Supply voltage limits	19.2...30 V
Input current	430 mA for supply circuit
Nominal output current	0.575 A at 60...70 °C 1.2 A
Output voltage	5.25 V DC (tolerance: +/- 0.21 %) for logic bus
Marking	CE
Overvoltage category	II
Status LED	1 LED (green)FIPRUN 1 LED (green)island state (RUN) 1 LED (green)power supply (PWR) 1 LED (red)FIPERR 1 LED (red)module error (ERR) 1 LED (yellow)test mode
Depth	70 mm
Height	40 mm
Width	128.3 mm
Net weight	0.145 kg

Environment

Electromagnetic compatibility	Immunity to electromagnetic interference conforming to IEC 61131-2
Product certifications	CSA C-Tick ATEX Cat 3G UL FM Class 1 Division 2
Pollution degree	2 conforming to IEC 60664-1
Operating altitude	<= 2000 m
IP degree of protection	IP20 conforming to EN 61131-2 class 1
Ambient air temperature for operation	0...60 °C (without derating) -25...70 °C (with derating factor)
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % at 60 °C without condensation
Vibration resistance	3 gn at 58...150 Hz on 35 x 7.5 mm symmetrical DIN rail 5 gn at 58...150 Hz on 35 x 15 mm symmetrical DIN rail +/-0.35 mm at 10...58 Hz
Shock resistance	30 gn for 11 ms conforming to IEC 88 reference 2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	135 g
Package 1 Height	2.5 cm
Package 1 width	8 cm
Package 1 Length	13 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

