BMEXBP0602H

rack X80 - 6 slots - Redundant PS - Ethernet backplane





Main

	Range of product	Modicon X80	
	Accessory / separate part type	Ruggedized rack	
	Product specific application	For severe environments	

Complementary

Number of slots	6 bus X + Ethernet	
Product compatibility	BMX processor Specific application module BMXCPS4002 BME processor I/O module	
Power consumption in W	191 MW 3.3 V DC 3.6 W 24 V DC	
Electrical connection	1 connector (XBE) expansion module	
Fixing mode	By 4 screws - diameter: 4.326.35 mm, mounting on panel By 4 M6 screws, mounting on plate By clips, mounting on 35 mm symmetrical DIN rail	
Current consumption	152 mA at 24 V DC 58 mA at 3.3 V DC	
MTBF reliability	201000 H	
Net weight	1.02 kg	

Environment

IP degree of protection	IP20
Ambient air temperature for operation	-2570 °C
Relative humidity	595 % without condensation
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive
Product certifications	CE UL CSA RCM EAC Merchant Navy ATEX zone 2/22 IECEx zone 2/22
Standards	EN/IEC 61131-2 EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201 IACS E10 EN/IEC 61000-6-5, interface type 1 and type 2 EN/IEC 61850-3, location G EN/IEC 60079-0

Environmental characteristic	Gas resistant class Gx conforming to ISA S71.04
	Gas resistant class 3C4 conforming to IEC 60721-3-3
	Dust resistant class 3S4 conforming to IEC 60721-3-3
	Sand resistant class 3S4 conforming to IEC 60721-3-3
	Salt resistant level 2 conforming to IEC 68252
	Mold growth resistant class 3B2 conforming to IEC 60721-3-3
	Fungal spore resistant class 3B2 conforming to IEC 60721-3-3
	Hazardous location class I division 2
Protective treatment	Conformal coating

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.033 kg	
Package 1 Height	7 cm	
Package 1 width	15.5 cm	
Package 1 Length	46 cm	
Unit Type of Package 2	S04	
Number of Units in Package 2	9	
Package 2 Weight	10 kg	
Package 2 Height	30 cm	
Package 2 width	40 cm	
Package 2 Length	60 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins