Product data sheet Characteristics

TM5SPS10FS

Power distribution module, Modicon TM5, for I/O 24 V DC, 1 Safety related output





Main

Range of product	Modicon TM5
Product or component type	Power distribution module
Product specific application	Supply 24 V DC I/O modules

Complementary

Complementary		
Range compatibility	Modicon M258 Modicon LMC058	
Product compatibility	Motion controller Logic controller	
[Us] rated supply voltage	24 V	
Network type	DC	
Current supplied	10 A for I/O power segment	
Maximum power dissipation in W	0.8 W	
Colour	Red	
Short-circuit protection	10 A external fuse	
Current consumption	<= 25 mA 24 V DC	
Marking	CE	
Net weight	0.061 kg	

Environment

Environment	
Standards	IEC 61131-2 UL 508 CSA C22.2 No 142 CSA C22.2 No 213
Product certifications	CULus CSA
Ambient air temperature for operation	-1055 °C without derating (horizontal installation) 5560 °C with derating factor (horizontal installation) -1050 °C (vertical installation)
Ambient air temperature for storage	-2570 °C
Relative humidity	595 % without condensation
Operating altitude	02000 m
Storage altitude	03000 m
Vibration resistance	1 gn at 8.4150 Hz on DIN rail 3.5 mm at 58.4 Hz on DIN rail
Shock resistance	15 gn for 11 ms
Resistance to electrostatic discharge	4 KV on contact conforming to EN/IEC 61000-4-2 8 kV in air conforming to EN/IEC 61000-4-2
Resistance to electromagnetic fields	1 V/M 22.7 GHz conforming to EN/IEC 61000-4-3 10 V/m 802000 MHz conforming to EN/IEC 61000-4-3

Resistance to fast transients	1 KV (I/O) conforming to EN/IEC 61000-4-4 1 KV (shielded cable) conforming to EN/IEC 61000-4-4 2 kV (power lines) conforming to EN/IEC 61000-4-4	
Surge withstand	0.5 KV differential mode conforming to EN/IEC 61000-4-5 1 kV common mode conforming to EN/IEC 61000-4-5	
Electromagnetic compatibility	EN/IEC 61000-4-6	
Disturbance radiated/conducted	CISPR 11	
Packing Units		
Package 1 Weight	0.061 kg	
Package 1 Height	31.000 mm	
Package 1 width	60.000 mm	
Package 1 Length	104.000 mm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes