



### Main

|                                |                  |
|--------------------------------|------------------|
| Range of product               | Canalis          |
| Product or component type      | Feed unit        |
| BAR MATERIAL                   | Aluminium        |
| Product compatibility          | KBB              |
| [Ie] rated operational current | 25 A<br>40 A     |
| Mounting location              | Right            |
| Colour                         | White (RAL 9003) |

### Complementary

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| Protection type                | Without protection                                                    |
| [Ue] rated operational voltage | 230...400 V                                                           |
| Connections - terminals        | Terminal block - Pg 21 - screw clamp connector for 10 mm <sup>2</sup> |
| Control type                   | Communicating                                                         |
| Number of circuits             | 1                                                                     |
| Provided equipment             | End cover                                                             |
| Mounting mode                  | By clips                                                              |
| Mounting support               | Busbar                                                                |
| Standards                      | IEC 60439-2<br>IEC 61439-6                                            |
| Width                          | 244 mm                                                                |
| Depth                          | 75.5 mm                                                               |
| Height                         | 75.5 mm                                                               |
| Net weight                     | 500 g                                                                 |

### Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
|-------------------------|------------------------------|

### Packing Units

|                              |       |
|------------------------------|-------|
| Unit Type of Package 1       | PCE   |
| Number of Units in Package 1 | 1     |
| Package 1 Weight             | 464 g |
| Package 1 Height             | 8 cm  |
| Package 1 width              | 8 cm  |
| Package 1 Length             | 27 cm |

### Offer Sustainability

|                          |                                |
|--------------------------|--------------------------------|
| Sustainable offer status | Green Premium product          |
| REACH Regulation         | REACH Declaration              |
| REACH free of SVHC       | Yes                            |
| EU RoHS Directive        | Compliant  EU RoHS Declaration |
| Toxic heavy metal free   | Yes                            |
| Mercury free             | Yes                            |

|                             |                                                                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| RoHS exemption information  |  <a href="#">Yes</a>                            |
| China RoHS Regulation       |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure    |  <a href="#">Product Environmental Profile</a> |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins     |
| PVC free                    | Yes                                                                                                                             |
| Halogen content performance | Halogen free product                                                                                                            |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|