




Main

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	FL21 gland plate
[Ie] rated operational current	100 A 160 A 250 A
Mounting location	Central
Colour	White (RAL 9001)

Complementary

Protection type	Without protection
[Ue] rated operational voltage	230...690 V
Connections - terminals	Lug for 240 mm ² flexible Lug for 240 mm ² rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By screws
Mounting support	Busbar
Standards	IEC 61439-6 IEC 60439-2
Width	585 mm
Depth	173.5 mm
Height	436 mm
Body material	Metal
Net weight	12.9 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.7 kg
Package 1 Height	20.5 cm
Package 1 width	48 cm
Package 1 Length	63.3 cm
Unit Type of Package 2	P06
Number of Units in Package 2	5
Package 2 Weight	74.9 kg
Package 2 Height	82 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	PAL

Number of Units in Package 3	5
Package 3 Weight	74.9 kg
Package 3 Height	60 cm
Package 3 width	80 cm
Package 3 Length	82 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

