



Main

Range of product	Canalis
Product name	KN
Product or component type	Electrical and mechanical jointing
Product compatibility	KN
[I _e] rated operational current	40 A 63 A
Offer type	Spare part
Colour	White (RAL 9001)

Complementary

Device application	Low power distribution
[U _e] rated operational voltage	230...500 V
Control type	Communicating
Number of circuits	1
Width	200 mm
Depth	38 mm
Height	100 mm
Net weight	600 g

Environment

IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP55 conforming to IEC 60529
Standards	IEC 61439-6 IEC 60439-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	640 g
Package 1 Height	4 cm
Package 1 width	10.2 cm
Package 1 Length	20 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Weight	9.42 kg
Package 2 Height	15.8 cm
Package 2 width	28.5 cm
Package 2 Length	43.5 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	15
Package 3 Weight	95.2 kg
Package 3 Height	16 cm
Package 3 width	29 cm
Package 3 Length	44 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------