



### Main

Range of product	Canalis
Product name	KS
Product or component type	Electrical and mechanical jointing
Product compatibility	KS
[I <sub>e</sub> ] rated operational current	500 A 630 A
Offer type	Spare part
Colour	White (RAL 9001)

### Complementary

Device application	Medium power distribution
[U <sub>e</sub> ] rated operational voltage	230...690 V
Control type	Without
Number of circuits	1
Busbar trunking polarity	3L + N + PE
Width	276 mm
Depth	117 mm
Height	167 mm
Net weight	4.35 kg

### Environment

IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP55 conforming to IEC 60529
Standards	IEC 61439-6 IEC 60439-2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.3 kg
Package 1 Height	15 cm
Package 1 width	18.5 cm
Package 1 Length	28 cm
Unit Type of Package 2	P06
Number of Units in Package 2	20
Package 2 Weight	134.5 kg
Package 2 Height	50 cm
Package 2 width	80 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

