Product data sheet Characteristics

KBB40ZFC6 CLOSED RING





Main

Range of product	Canalis
Product or component type	Ring
Product compatibility	KBA KBB
Fixing device mounting	Mounted on the luminaire
Maximum load	45 kg
Quantity per set	Set of 10

Complementary

Accessory / separate part category	Fixing accessory
Thread type	M5
Width	22 mm
Height	70 mm
Net weight	50 g

Environment

Standards	IEC 61439-6	
	IEC 60439-2	

Packing Units

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	15 g
Package 1 Height	1 cm
Package 1 width	10 cm
Package 1 Length	10 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	165 g
Package 2 Height	5 cm
Package 2 width	3 cm
Package 2 Length	11 cm
Unit Type of Package 3	P06
Number of Units in Package 3	9000
Package 3 Weight	156.298 kg
Package 3 Height	77 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☐ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
PVC free	Yes	
Halogen content performance	Halogen free product	

18 months

KBB40ZFC6

