



Main

Range of product	Canalis
Product name	KS
Product or component type	Fixing bracket
Product compatibility	KS
Fixing device mounting	Suspended on threaded rod Wall mounting
Maximum load	70 kg
Quantity per set	Set of 10

Complementary

Accessory / separate part category	Fixing accessory
[Ie] rated operational current	400.0 A
Width	30 mm
Depth	92 mm
Height	183 mm
Net weight	300 g

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	230 g
Package 1 Height	17 cm
Package 1 width	18.5 cm
Package 1 Length	19 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	2.35 kg
Package 2 Height	17 cm
Package 2 width	18.5 cm
Package 2 Length	19 cm
Unit Type of Package 3	P06
Number of Units in Package 3	450
Package 3 Weight	111 kg
Package 3 Height	65 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

