



Main

Range of product	Canalis
Product or component type	Busbar trunking
Busbar description	Flexible length
Product compatibility	KBB
Direction change type	3 dimensions
[Ie] rated operational current	40 A at 35 °C

Complementary

Device application	Lighting Power socket distribution
Thermal stress limit	900 kA ² .s
Maximum radiated magnetic field	2 pT
[Ue] rated operational voltage	230...400 V
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	0.94 kA
[Ipk] rated peak withstand current	9.6 kA
THDI	0...15 % 40 A 15...33 % 32 A 33...100 % 28 A
Network frequency	50/60 Hz
Control type	Communicating
Number of circuits	1
Mounting mode	By clips
Standards	IEC 61439-6 IEC 60439-2
Width	2.14 m
Depth	51 mm
Height	60 mm
Length	2 m
Colour	White (RAL 9003)
Net weight	1.9 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK06 conforming to IEC 62262
Ambient air temperature for operation	0...35 °C without derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.2 kg
Package 1 Height	6 cm
Package 1 width	44 cm
Package 1 Length	61 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------