



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Rising main
BAR MATERIAL	Aluminium
Device application	Rise medium power distribution
[Ie] rated operational current	500 A at 35 °C
Number of tap-off outlets	4

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	26.2 kA
[Ipk] rated peak withstand current	55 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.66 µT
Thermal stress limit	733 kA².s
THDI	0...15 % 500 A 15...33 % 400 A 33...100 % 315 A
Maximum voltage drop	<0.013 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.014 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Vertical - neutral on right
Neutral position	Right
Busbar trunking polarity	3L + N + PE
Dimension type	Fix
Width	146 mm
Depth	113 mm
Height	2.5 m
Net weight	30.7 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	34.7 kg
Package 1 Height	12.2 cm
Package 1 width	16.8 cm
Package 1 Length	263.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

