



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Transport length
BAR MATERIAL	Copper
Device application	Medium power distribution
[Ie] rated operational current	250 A at 35 °C
Number of tap-off outlets	0

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uiimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	10 kA
[Ipk] rated peak withstand current	28 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.69 µT
Thermal stress limit	100 kA ² .s
THDI	0...15 % 250 A 15...33 % 200 A 33...100 % 160 A
Maximum voltage drop	<0.0259 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0255 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0254 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0253 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + PEN 3L + N + PE
Dimension type	Made to measure
Width	146 mm
Depth	54 mm
Length	500...1995 mm
Net weight	14 kg

Environment

Standards	IEC 61439-6 IEC 60439-2
-----------	----------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	16 kg
Package 1 Height	6.4 cm
Package 1 width	16.7 cm
Package 1 Length	208.3 cm