



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Transport length
BAR MATERIAL	Copper
Device application	Medium power distribution
[Ie] rated operational current	400 A at 35 °C
Number of tap-off outlets	0

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	18.8 kA
[Ipk] rated peak withstand current	49.2 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	1 µT
Thermal stress limit	354 kA².s
THDI	0...15 % 400 A 15...33 % 315 A 33...100 % 250 A
Maximum voltage drop	<0.0184 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0179 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0177 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0176 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + PEN 3L + N + PE
Dimension type	Made to measure
Width	146 mm
Depth	54 mm
Length	500...1995 mm
Net weight	20 kg

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	25 kg
Package 1 Height	6.4 cm
Package 1 width	16.7 cm
Package 1 Length	208.3 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product