



### Main

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBA KBB
Device application	Lighting
Range compatibility	KBA busbar trunking KBB busbar trunking

### Complementary

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Busbar trunking polarity	L2 + L1 + L3 + N + PE L + N + PE
Protection type	Fuse
Fuse type	Cylindrical: 8.5 x 31.5 mm - gG conforming to NF
Tap-off lock colour	Blue
Tap-off unit polarity	L2 + N + PE L3 + N + PE L1 + N + PE
Tap-off unit connector type	With phase selection
Provided equipment	Fuse not supplied
Standards	EN/IEC 61439-6 EN/IEC 60439-2
Width	168 mm
Depth	33 mm
Height	53 mm
Colour	Cream (RAL 9001)
Net weight	90 g
Quantity per set	Set of 10

### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	94 g
Package 1 Height	6 cm
Package 1 width	5.2 cm
Package 1 Length	14 cm
Unit Type of Package 2	BB1

Number of Units in Package 2	10
Package 2 Weight	1.01 kg
Package 2 Height	12 cm
Package 2 width	16 cm
Package 2 Length	25 cm
Unit Type of Package 3	P06
Number of Units in Package 3	440
Package 3 Weight	53.16 kg
Package 3 Height	62 cm
Package 3 width	80 cm
Package 3 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------

