

Product data sheet

Characteristics

KBC16DCF40

Canalis - tap-off unit - 16A - 3L+N+PE - with protection



Main

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBA KBB
Device application	Lighting
Range compatibility	KBB busbar trunking KBA busbar trunking

Complementary

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Busbar trunking polarity	L2 + L1 + L3 + N + PE
Protection type	Fuse
Fuse type	Cylindrical: 8.5 x 31.5 mm - gG conforming to NF
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Provided equipment	Fuse not supplied
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	205 mm
Depth	38 mm
Height	68 mm
Colour	Cream (RAL 9001)
Net weight	90 g

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	237 g
Package 1 Height	7.5 cm
Package 1 width	8 cm
Package 1 Length	17 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	18
Package 2 Weight	4.7 kg
Package 2 Height	15.8 cm
Package 2 width	28.5 cm

Package 2 Length	43.5 cm
Unit Type of Package 3	P06
Number of Units in Package 3	144
Package 3 Weight	38 kg
Package 3 Height	73 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

