



Main

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBB KBA
Device application	Power socket distribution
Range compatibility	KBA busbar trunking KBB busbar trunking

Complementary

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Busbar trunking polarity	L2 + L1 + L3 + N + PE
Protection type	Fuse
Fuse type	Cylindrical: 8.5 x 31.5 mm - gG conforming to NF
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Tap-off unit socket description	NF 2P+E 10/16 A 250V
Provided equipment	Fuse not supplied
Standards	EN/IEC 61439-6 EN/IEC 60439-2
Width	160 mm
Depth	53 mm
Height	68 mm
Colour	Grey (RAL 7035)
Net weight	90 g

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Packing Units

Package 1 Weight	0.250 kg
Package 1 Height	0.750 dm
Package 1 width	0.800 dm
Package 1 Length	1.600 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

