



### Main

|                                |                                                                                                                                                                    |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product               | Canalis                                                                                                                                                            |
| Range compatibility            | KN busbar trunking                                                                                                                                                 |
| Product or component type      | Tap-off unit                                                                                                                                                       |
| Busbar trunking compatibility  | Canalis KN busbar trunkingplug-in                                                                                                                                  |
| [Ie] rated operational current | 25 A at 35 °C                                                                                                                                                      |
| Protection type                | Fuse isolator: for aM cylindrical fuse, size 10 x 38 mm - 25 A conforming to NF<br>Fuse isolator: for gG cylindrical fuse, size 10 x 38 mm - 20 A conforming to NF |
| Provided equipment             | Fuse to be ordered separately<br>Cable clamp                                                                                                                       |
| Mounting mode                  | Plug-in with fixed polarity                                                                                                                                        |
| Tap-off unit polarity          | 3L+N+PE<br>3L+PE                                                                                                                                                   |
| Colour                         | White (RAL 9001)                                                                                                                                                   |

### Complementary

|                                        |                                                                                                  |
|----------------------------------------|--------------------------------------------------------------------------------------------------|
| Device application                     | Low power distribution                                                                           |
| [Ue] rated operational voltage         | 230...500 V depending on protective device                                                       |
| [Uimp] rated impulse withstand voltage | 4.6 kV                                                                                           |
| [Ui] rated insulation voltage          | 500 V depending on protective device                                                             |
| Network frequency                      | 50/60 Hz                                                                                         |
| Electrical connection                  | Cable clamp terminal 6 mm <sup>2</sup> flexible<br>Cable clamp terminal 10 mm <sup>2</sup> rigid |
| Door/cover opening side                | Front                                                                                            |
| Tap-off unit disconnection mode        | By drawing out                                                                                   |
| Standards                              | IEC 61439-1<br>IEC 61439-6                                                                       |
| Width                                  | 103 mm                                                                                           |
| Depth                                  | 48.8 mm                                                                                          |
| Height                                 | 161 mm                                                                                           |
| Net weight                             | 0.38 kg                                                                                          |

### Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 291 g   |
| Package 1 Height             | 7.8 cm  |
| Package 1 width              | 11.8 cm |
| Package 1 Length             | 15.8 cm |
| Unit Type of Package 2       | BB1     |
| Number of Units in Package 2 | 24      |
| Package 2 Weight             | 7.7 kg  |

|                              |            |
|------------------------------|------------|
| Package 2 Height             | 17 cm      |
| Package 2 width              | 40 cm      |
| Package 2 Length             | 60 cm      |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 384        |
| Package 3 Weight             | 133.872 kg |
| Package 3 Height             | 82.3 cm    |
| Package 3 width              | 80 cm      |
| Package 3 Length             | 120 cm     |

### Offer Sustainability

|                             |                                                                                                                             |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                       |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC          | Yes                                                                                                                         |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free      | Yes                                                                                                                         |
| Mercury free                | Yes                                                                                                                         |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                                                                                      |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                               |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product                                                                                                        |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|