




Main

Range of product	Canalis
Product name	KS
Product or component type	Empty tap-off unit
Product compatibility	KS
[Ie] rated operational current	160 A at 35 °C
Tap-off unit polarity	3L+PEN

Complementary

Device application	Low power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Tap-off unit disconnection mode	By drawing out
Tap-off unit connector type	With fixed polarity
Door opening size	630.5 mm
Door opening side	Right
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Standards	IEC 60439-2 IEC 61439-6
Body material	Metal
Colour	White (RAL 9001)
Width	482 mm
Depth	207 mm
Height	332 mm
Net weight	8 kg

Environment

Earthing system	TN-C - busbar trunking TN-C - tap-off unit
-----------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	11.4 kg
Package 1 Height	26 cm
Package 1 width	34 cm
Package 1 Length	49 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

