




Main

Range of product	Canalis
Range compatibility	KS busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunkingplug-in
[Ie] rated operational current	32 A
Protection type	Circuit breaker: miniature circuit breaker (MCB)
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

Complementary

Device application	Medium power distribution
Provided equipment	Circuit breaker to be ordered separately Blanking plate
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	400 V depending on protective device 500 V depending on protective device 690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Pre-wired terminal block - ISO32 6 mm ² flexible Pre-wired terminal block - ISO32 10 mm ² rigid
Door/cover opening side	Front
Tap-off unit disconnection mode	By drawing out
Standards	IEC 61439-6 IEC 61439-1
Body material	Plastic
18 mm pitches	5
Width	135 mm
Depth	108 mm
Height	175 mm
Net weight	0.6 kg

Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Package 1 Weight	0.650 kg
Package 1 Height	1.600 dm
Package 1 width	1.750 dm
Package 1 Length	1.360 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

